

## Product Specifications

|   |   |
|---|---|
| Product:                                      | Contexture  |
| Date:   | May 2006  |
| Description:                                  | Fine gauge, low profile high density<br>Textured patterned loop                                 |
| Pile Fibre:                                   | Honeywell, Zeftron Solure,<br>100% B.C.F. Solution Dyed Nylon                                   |
| Yarn Quality:                                 | 3 Ply Type 6 resultant 4293 decitex air entangled   |
| Gauge:  | 2.54 mm (1/10")   |
| Stitch Rate:                                  | 44.5 per 100mm  |
| Pile Mass:                                    | 949 gm/m <sup>2</sup> (28 oz/yd <sup>2</sup> )  |
| Pile Height:                                  | 3.9 mm  |
| Primary Backing:                              | 112 g/m <sup>2</sup> (3.3 oz/yd <sup>2</sup> ) 28x16 woven polypropylene                        |
| Secondary Backing:                            | 108 g/m <sup>2</sup> (3.3 oz/yd <sup>2</sup> ) actionbac  |
| Laminate:                                     | 949 g/m <sup>2</sup> (28 oz/yd <sup>2</sup> ) synthetic latex                                   |
| Total Weight:                                 | 8.04 kg/LM (62.8 oz/yd <sup>2</sup> )   |
| Width:  | 3.66 metres (broadloom)   |
| A.C.C.S. Reg. No.:                            | 23070   |
| A.C.C.S. Grade:                               | Residential Extra Heavy Duty 2 (Stairs) - 6 Star<br>Contract Extra Heavy Duty (Stairs) - 4 Star |
| Critical Radiant Flux:<br>(Burning Behaviour) | CHF Mean Result 11 kw/m <sup>2</sup> (Direct Stick)<br>Smoke Value 11% min (Direct Stick)       |
| AS/ISO 9239-1:2003<br>Part 1 - Test           | Passes requirements of BCA spec C1.10a<br>Class 9a; 9b; 9c Buildings (Direct Stick)             |
| Dichloromethane Extract:<br>(AS 2001.3.4)     | 0.8% maximum  |
| Resistance to Insect Pests:<br>(AS 2001.6.1)  | Pass (inherently resistant)   |
| Tuft withdrawal Force:<br>(AS 2111.15)        | 30 Newtons (minimum)  |
| Secondary Backing Adhesion:<br>(AS 2111.16)   | 30 Newtons (minimum)  |

## Warranties\*

- Lifetime stain removal guarantee
- Lifetime warranty against fibre loss
- Lifetime colourfast warranty
- Lifetime atmospheric contaminants warranty
- Lifetime anti-static warranty

\*These are LIMITED Warranties. Please see full warranty details.

**Installation:** All carpet installations are to be in accordance with AS2455.1:1995 unless otherwise stated in writing by Tuftmaster Carpets.

Carpet is a textile that is subjected to extreme variations in temperature and tension in the manufacturing process. During this process variances may occur in both the width and length of this patterned carpet and as a result an exact pattern match cannot be guaranteed. A reasonable pattern match may be obtained when installing carpet conventionally over an underlay and when installed by trained, experienced and professional carpet layers. Pattern matching cannot be guaranteed when installed by the direct stick or dual bond method as this only allows for minor stretching and adjustments of the pattern during installation. When installing patterned carpets on open floors it is a requirement that the carpet layers have unrestricted access to the entire floor being laid. The initial run of carpet on any type of installation is the most critical and ensures that the project is set out accurately prior to joining, to ensure the best possible pattern match over the entire floor area is achieved. No acceptable pattern match can be guaranteed if the carpet layers are only provided part floors at a time.

**Carpet Joins:** Tuftmaster Carpets specify that when laying conventionally or dual bond that all cut edges to be joined must be tipped with an edge sealing latex adhesive (minimum 60% component) and be given sufficient time to cure properly prior to heat taping (time is dependant on site conditions and temperature). It is the installers responsibility to ensure that the correct heat tapes are used when installing carpet by both methods.

**Dye Variation:** Shade or pattern variations may occur from sample and between dye lots and within production runs due to the many variances in the manufacturing of carpet, however these variations will be within recognized textile industry standards.

**Dye Variation:** Carpet should be cleaned and maintained in accordance with AS 3733:1995.1.



### HEAD OFFICE

### TUFTMASTER CARPETS PTY. LTD.

A.C.N. 004 802 564

Cope Street, Preston, Victoria 3072.

Telephone: 61 3 9791 1388

Facsimile: 61 3 8480 4080

Email: email@tuftmaster.com.au

### Interstate Offices

N.S.W.  
(02) 9555 2177

Queensland  
0402 119 538  
1800 062 076

S.A.  
0402 119 541

W.A.  
0402 119 545

Tasmanian Agent  
(03) 6234 9855

**Honeywell**  
**zeftron**



WASTE WISE IS A PROGRAM OF  
SUSTAINABILITY VICTORIA



QUALITY ASSURED COMPANY



AS 3901 / ISO 9001 / NZS 9001  
REGN. NO. 072