

Product Specifications

Product:	Degree
Date:	May 2005
Description:	Fine Gauge, Low Profile, Level Loop Heather
Pile Fibre:	100% Selected Carpet Wools
Fibre Quality:	Semi Worsted, Multi-ply Twisted and Non Heat Set
Gauge:	3.175 mm (1/8")
Stitch Rate:	41.8 per 100 mm
Pile Mass:	1356 gm/m ² (40 oz/lyd ²)
Pile Height:	5.0 mm
Colouration:	Stock Dyed
Primary Backing:	112 g/m ² (3.3 oz/lyd ²) Heat Stabilised Woven Polypropylene
Secondary Backing:	237 g/m ² (7 oz/lyd ²) Woven Jute
Laminate:	948 g/m ² (28 oz/lyd ²) Synthetic Latex
Total Weight:	9.7 kg/LM (78.3 oz/lyd ²)
Width:	3.66 metres
A.C.C.S. Reg. No:	
A.C.C.S. Grade:	Residential Extra Heavy Duty (Stairs) - 6 Star Commercial Heavy Duty, (Stairs) - 3 Star In accordance with AS 2001.6.1
Moth Proofed:	
Critical Radiant Flux: (Burning Behaviour)	CHF Mean Result kw/m ² (Direct Stick) Smoke Value % min (Direct Stick)
AS/ISO 9239-1:2003	Part 1 - Test
BS 1006.B02:	Colourfastness to light 5
AS 2111.19.2:	Colourfastness to shampoo 3-4
AS 2111.19.1:	Colourfastness to rubbing 3-4
AS 2111.4.16:	Colourfastness to solvents 3-4
Product Features:	<ul style="list-style-type: none"> • 8 neutral tonings in a contemporary textured finish. • Increases thermal and acoustic comfort. • Superior appearance retention when correctly maintained. • The use of chair pads is mandatory when used in commercial installations. • Virtually unlimited custom colour option. • Must be laid in accordance with AS/NZS 2455.1.1995 • Subject to Tuftmaster's 'Terms of Trading.'

Also available in 48oz

Shift Lines: The construction of this graphics design loop imparts shift lines across the width. Certain light sources shining across the surface may accentuate the effect by forming shadow lines. This effect is not a manufacturing fault and will not detract from the carpets performance.

Installations Carpet is a textile material that is subjected to variations in temperature and tension in the finishing process which may affect standard to AS/NZS 2455.1.1995 manufacturing tolerances.

During this process variances may occur in both the width and length of patterned carpets and as a result of this exact pattern matching cannot always be guaranteed.

Pattern matching will be more readily achieved when conventionally installing carpet over a commercial underlay and when installed by trained, experienced and professional carpet layers. Pattern match cannot be guaranteed by Tuftmaster Carpets when the carpet is installed by either the direct stick or double direct stick (dual bond) method. These installation systems allow only minor stretching and adjustment of the pattern.

When installing patterned carpets on open floors it is a requirement that the carpet installers have unrestricted access to the entire floor area being installed. This will ensure that the carpet can be set out accurately prior to joining and to ensure the best possible pattern match being achieved. No pattern match can be guaranteed if the carpet installers are only provided with part of the floor to install at any one time.

Seam Sealing: Seam sealer must be applied to every seam and all trimmed joins when direct sticking to the floor, and when dual bonding or double bonding in accordance with AS/NZS 2455.1.1995

This carpet passes the requirements of the BCA Spec. C1.10a for use in all Class 9a; 9b; 9c Buildings. Test certificates can be supplied upon request.

Cleaning: Carpet should be cleaned and maintained in accordance with AS 3733 : 1995.1, and / or as instructed by Tuftmaster Carpets Pty Ltd.



HEAD OFFICE TUFTMASTER CARPETS PTY. LTD.

A.C.N. 004 802 564
Cope Street, Preston, Victoria 3072.
Telephone: 61 3 9791 1388
Facsimile: 61 3 8480 4080
Email: email@tuftmaster.com.au

Interstate Offices

N.S.W. (02) 9555 2177 Queensland 0402 119 538 1800 062 076 S.A. 0402 119 541	W.A. 0402 119 545 Tasmanian Agent (03) 6234 9855
---	---

