

Product Specifications

Product:	Phoenician 48
Date:	October 2006
Description:	Low profile, High density, Fine gauge patterned loop pile
Pile Fibre:	90% Selected Carpet Wools 10% BCF Anti-static Nylon
Fibre Quality:	Semi Worsted spun, Multiply, Twisted and Non-heat set
Gauge:	3.175mm (1/8")
Stitch Rate:	47.2 per 100mm
Pile Weight:	1627 gm/m2 (48 oz/yd2)
Pile Height:	5.0 mm
Colouration:	90% Stock dyed 10% Accent space dyed
Primary Backing:	114 g/m2 (3.3 oz/yd2) Heat stabilised woven Polypropylene
Secondary Backing:	305 g/m2 (9 oz/yd2) Woven Jute
Laminate:	956 g/m2 (28.2 oz/yd2) Synthetic latex
Total Weight:	10.99 kg/LM (88.6 oz/yd2)
Width:	3.66 metres
A.C.C.S. Reg No:	95051
A.C.C.S. Grade:	Residential Extra Heavy Duty 2 (Stairs) - 6 Star Contract Extra Heavy Duty (Stairs) - 3 Star
Moth Proofed:	In accordance with AS 2001.6.1
AS 1530.3:	Ignitability 14 : Range 0-20 Spread of Flame 0 : Range 0-10 Heat Evolved 1 : Range 0-10 Smoke Developed 3 : Range 0-10
BS 1006-B02:	Colourfastness to Light 5 - 6
AS 2111.19.2:	Colourfastness to Shampoo 4 - 5
AS 2111.19.1:	Colourfastness to Rubbing 3 - 4
AS 2001.4.16:	Colourfastness to Solvents 4 - 5

Product Specifications

Product:	Phoenician 40
Date:	August 2003
Description:	Low profile, High density, Fine gauge patterned loop pile
Pile Fibre:	90% Selected Carpet Wools 10% BCF Anti-static Nylon
Fibre Quality:	Semi Worsted spun, Multiply, Twisted and Non-heat set
Gauge:	3.175mm (1/8")
Stitch Rate:	37.2 per 100mm
Pile Weight:	1356 gm/m2 (40 oz/yd2)
Pile Height:	4.8 mm
Colouration:	90% Stock dyed 10% Accent space dyed
Primary Backing:	114 g/m2 (3.3 oz/yd2) Heat stabilised woven Polypropylene
Secondary Backing:	305 g/m2 (9 oz/yd2) Woven Jute
Laminate:	956 g/m2 (28.2 oz/yd2) Synthetic latex
Total Weight:	10 kg/LM (80.6 oz/yd2)
Width:	3.66 metres
A.C.C.S. Reg No:	95050
A.C.C.S. Grade:	Residential Extra Heavy Duty 1 (Stairs) - 5 Star Contract Medium Duty (Stairs) - 2 Star
Moth Proofed:	In accordance with AS 2001.6.1
AS 1530.3:	Ignitability 15 : Range 0-20 Spread of Flame 0 : Range 0-10 Heat Evolved 1 : Range 0-10 Smoke Developed 2 : Range 0-10
BS 1006-B02:	Colourfastness to Light 5
AS 2111.19.2:	Colourfastness to Shampoo 4 - 5
AS 2111.19.1:	Colourfastness to Rubbing 3 - 4
AS 2001.4.16:	Colourfastness to Solvents 4 - 5

*Product Features: Increases thermal and acoustic comfort
Superior appearance retention when correctly maintained
Available in 7 serviceable designer colourations*

*Notes:
Seam Sealer to be used on all seams
The use of chair pads are mandatory
Must be laid in accordance with AS 2455
Subject to Tuftmaster's 'Terms of Trading'
SHIFT LINES: The nature of the construction of this patterned
loop pile carpet imparts shift lines across the width. Certain
light sources shining across the surface may accentuate the
effect by forming shadow lines. This effect is not a manufacturing
fault and will not detract from the carpets performance.*

HEAD OFFICE

TUFTMASTER CARPETS PTY. LTD.

A.C.N. 004 802 564

Cope Street, Preston, Victoria 3072.

Telephone: 61 3 9791 1388

Facsimile: 61 3 8480 4080

Email: email@tuftmaster.com.au

Interstate Offices

N.S.W.
(02) 9555 2177

Queensland
0402 119 538
1800 062 076

S.A.
0402 119 541

W.A.
0402 119 545

Tasmanian Agent
(03) 6234 9855

